



DENSO VISCOTAQ™ SELF-HEALING COATINGS

ULTIMATE VISCO-ELASTIC COATING & SEALANT

SUITABLE FOR:

- Buried Pipelines and Fittings
- Above Ground Structures and Pipework
- Weld Joints
- Flanges and Valves
- Tank Chimes
- Waterproofing and More





A PATENTED UNIQUE VISCO-ELASTIC AMORPHOUS A-POLAR POLYOLEFIN FOR THE PROTECTION OF ABOVE AND BELOW GROUND SUBSTRATES AGAINST CORROSION.

Developed in cooperation with leading oil and gas companies and polymer engineers to meet the demand for new viscous elastic coating technology, for the protection of shaped and non-shaped substrates.

SYSTEM FEATURES:

- Visco-elastic amorphous apolar polyolefin
- Failure-free application and UV resistant
- No primer needed
- Immediate adhesion to substrate
- Permanent wetting characteristics and no cure time
- Never cracks or becomes brittle & conforms to irregular shapes and more
- No VOCs



PUB No. 573.07.21



FM 01548 | EMS 583748
ISO 9001:2015 & ISO 14001:2015

WINN & COALES (DENSO) LTD

TEL: +44 (0) 208 670 7511
FAX: +44 (0) 208 761 2456
EMAIL: mail@denso.net
WEB: www.denso.net

Winn & Coales (Denso) Ltd
33 - 35 Chapel Road
London SE27 0TR
UNITED KINGDOM



A MEMBER OF WINN & COALES INTERNATIONAL