

FILOseal+HD

universal re-enterable duct sealing system duct opening up to Ø 250 mm

- **Larger sizes available upon request**
- Up to 2 bar Pressure Resistance
- 100Kg pulling Force on the cables when sealed
- 10xd at 45°, with 1 bar pressure bending test

FiloSeal+HD provides a strong support system using the hexagonal tubes which builds up like a honeycomb structure. FiloSeal+HD is suitable for sealing any cable configuration or pipes contained in one duct and also allows easy re-entry of the seal to add or remove cables or pipes as required. The Filoform duct sealing system FiloSeal+HD uses our MD+ sealant which is easily applied from a skeleton gun. The high quality, one component, flexible sealant "MD+" is based on a silicon compound that cures with air (Humidity). The unique design of the hexagonal tubes makes positioning and separation of the cables very simple while also providing a strong backing for the MD+ to be applied on.

FEATURES

- High levels of Gas and Water tightness Excellent adhesion, applicable to all common building materials
- Shows Fire resistance properties
- Resistant to Hydrogen Sulphide / Methane and

- Shock absorbing
- Non toxic, neutral and almost odourless
- Suitable for any shaped duct / bore hole / opening Quick and easy installation
- cables, PILC, (HD) PE pipes
- Suitable for renovations, can be installed
- Resistant to Rats
- Resistant to termites (Mastotermes Darwiniensis) Northern Australian termites
- Resistant to hydrocarbons

Product Name	Duct diameter minmax. (mm)	Order unit
FiloSeal+HD - 75 mm > 110 mm	Ø 110 max.	per piece
FiloSeal+HD - 125 mm > 160 mm	Ø 160 max.	per piece
FiloSeal+HD - 180 mm	Ø 180 max.	per piece
FiloSeal+HD - 200 mm	Ø 200 max.	per piece
FiloSeal+HD - 225 mm	Ø 225 max.	per piece
FiloSeal+HD - 250 mm	Ø 250 max.	per piece